Product information

Motorbike 4T 20W-50 Street



Description

Heavy-duty motor oil based on selected mineral oils. Ensures optimum performance and protection of the engine under all operating conditions. Reliable lubrication, optimum noise damping and low wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

Properties

- miscible with all commercially available motor oils
- optimum stability to aging
- oil film strength
- prevents black sludge
- high wear resistance
- high shear stability
- especially suitable for wet clutches
- excellent cleaning effect
- tested for catalytic converters
- low evaporation loss
- very good dispersion properties
- guarantees low oil consumption
- universal application

Specifications and approvals:

API SN Plus • JASO MA2

Technical data

SAE class (engine oils) 20W-50 SAE J300

Density at 15 °C 0,885 g/cm³

DIN 51757 Viscosity at 40 °C 156 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 18,00 mm²/s

ASTM D 7042-04

Viscosity at -15°C (CCS) <= 9500 mPas

ASTM D 5293

Viscosity index 128

DIN ISO 2909

Pour point -33 °C

DIN ISO 3016

Evaporation loss (Noack) 7,9 %

ASTM D 5800

Flash point 240 °C

DIN ISO 2592

Total base number 6,7 mg KOH/g

DIN ISO 3771

Sulfate ash 0,8 g/100g

DIN 51575



Technical data

Color number (ASTM) L 3,0

DIN ISO 2049

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to tough operating conditions. Suitable for engines with or without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

Available pack sizes

1 l Canister plastic 1500

BOOKLET

1 l Canister plastic 21251

ALGERIEN-GB-ARAB-F

1 l Canister plastic 20855

JΡ

4 l Canister plastic 1696

BOOKLET

20 l Canister plastic 1560 D-GB

60 l Drum sheet metal 1561

D-GB

205 l Drum sheet metal 3829

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871

www.liqui-moly.de